

Experimental Evaluation of Sour Gas Stream in a Packed Column in Gas Sweetening Units with Nano Bed

Ahamd Reza Gharibi¹, Arezoo Khosravi^{2, *}, Farshad Farahbod³

¹Department of Petroleum Engineering, Khomeinishahr Branch, Islamic Azad University, Khomeinishahr, Iran

²Department of Mechanical Engineering, Khomeinishahr Branch, Islamic Azad University, Khomeinishahr, Isfahan, Iran

³Department of Chemical Engineering, Firoozabad Branch, Islamic Azad University, Firoozabad, Iran

Abstract

Many natural gases are produced from wells containing hydrogen sulphide, sulphur compounds and carbon dioxide. Many different processes are used to treat raw natural gas to pipeline quality. Sulfur is commonly present as an impurity in fossil fuels. The sulfur compounds can threaten the pipe lines and all of the devices, severely. In addition, the mechanism of sulphur absorption by nano fluid in a packed bed under the magnetic field is considered, in this study. The experimental and theoretical investigation is done to obtain the outlet amount of sulphur in gas stream. A packed tower which is equipped by nano catalyst is used for sweetening of sour gas. Two gray 20 lit of volume pressurized vessel contain sour gas can be joint to the experimental line. In 40 cm of efficient volume of glass balls with 2.5 cm in diameter are used as the packing. Two meshes are applied for separating the reactor vessel to the three sections. One polymeric weir with mesh size of 0.02 cm is on the top of vessel as a holder to let the only treated gas stream. Results show, the amounts of hydrogen sulfide catch from branch line defined the process performance. The obtained results show, the higher value of friction factor causes higher values of pressure drops. Although the small changes in values of higher friction factor causes harp change in value of pressure drop.

Keywords

Gas Stream, Nano Bed, Packed Column, Operation Conditions, Sweetening Unit

Received: October 25, 2019 / Accepted: January 14, 2020 / Published online: February 20, 2020

@ 2020 The Authors. Published by American Institute of Science. This Open Access article is under the CC BY license.

<http://creativecommons.org/licenses/by/4.0/>

1. Introduction

There are a number of absorption gas treating processes, but the most common is the amine process in which acid gases react chemically. The 'rich' amine solution is heated under low pressure to regenerate the liquid by driving off the acid gases. Several different amine solutions can be used. A). Methyl-Diethanol Amine, B). MEA), C). Mono-ethanol Amine (MEA), D). Di-ethanol Amine (DEA), E). Di-glycol Amine (DGA), F). Alkanol Amine+Sulfinol. Many natural gases are produced from wells containing hydrogen sulphide, sulphur compounds and carbon dioxide. Perry and Chilton, et

al, 1999 these gases are treated prior to sale or entry to a process plant. A gas which has high concentration of sulphur compounds is called 'Sour' gas. The H₂S and CO₂ are known as acid gases, and are corrosive, if water or oxygen is present. The hydrogen sulphide H₂S must be removed from the Natural Gas before it can be used, due to the fact that it is highly corrosive and deadly toxic. The MDEA solution selectively removes the H₂S however, some of the CO₂ and sulphur compounds during the sweetening process also absorbed, CO₂ concentration in the first gas plant is below the allowable concentration for the pipe line specification (less than 5%).

* Corresponding author
E-mail address: mabbbeigloo@gmail.com (A. Khosravi)

1.1. Amine Sweetening Process

There is a number of absorption gas treating processes, but the most common is the amine process in which acid gases react chemically. The 'rich' amine solution is heated under low pressure to regenerate the liquid by driving off the acid gases. Several different amine solutions can be used. These amine mixtures have been called a variety of names including formulated amines and MDEA based amines. Historically, MDEA has been recognized primarily for its ability to selectively absorb H₂S from a gas while leaving large amounts of CO₂ in the gas. The selective absorption characteristics of MDEA have been widely reported in the above literature. Until the last few years, MDEA has not been associated with cases where the removal of large amounts of CO₂ is desired. The type of solution used in the process will depend upon the type and quantity of acid gas contained in the sour gas stream and the volume of sour gas to be treated. From Shall Operating Manual, 1983, Sirte Oil Company, the process flow diagram for Amine sweetening system show the process details carried upon the Sour gases in the plant. The GPSA (Gas Processors Suppliers Association), et al, 2004, the general operating problems in the amine system are centered around the following five major areas:

1. Amine loss from the system
2. Amine foaming problem
3. Corrosion problem
4. Concentration of residual gas in lean amine solution
5. Winterization.

1.2. Amine Loss from the System

A certain amount of MDEA will be continuously lost from the amine sweetening system due to the vapor pressure of the amine.

The largest amine losses are usually through the amine absorber as carry over with the treated gas. Some amine is also lost through the amine stripper, amine flash tank, pumps packing etc. The losses vary for different plants, but usually are between 0.05 to 0.5 gallons per MMscf of treated gas. These losses can be much higher depending upon several factors such as sour gas flow rate, reboiler temperature, high differential temperature between amine solution and the sour gas in the amine absorber, bad mist eliminator on the absorber top, bad filtration system and foaming. Here is some guidance to help in minimizing the amine solution losses from the system:

- a) Maintain the top temperature of the amine absorber as low as possible.
- b) Maintain proper amine solution concentration.

- c) Ensure good clean amine solution-good filtration, proper reboiler control to avoid chemical breakdown of amine and avoid all amine contamination. Regularly check all operating parameters & process variables to maintain steady running of the amine unit.

1.3. Amine Foaming

The foaming is a common problem that results in a decrease of treating capacity of the plant and amine losses. It is usually detected by a sharp rise in the pressure drop across the amine absorber. The amine foaming can occur from the reaction of the amine solution with organic acids or because of the presence of hydrocarbon contaminants, ferric sulphide, or other sludge. Several anti-foaming agents have been developed to combat this and some products which are primarily corrosion inhibitors have shown good anti-foaming properties. Where foaming is caused by hydrocarbon contamination, it may be eliminated by maintaining the temperature of the absorber above the hydrocarbon condensation temperature. Foaming can be prevented in the following ways:

- a). Do not overload the inlet separator in your plant.
- b). Avoid condensation of liquid hydrocarbons in the amine absorber by keeping the temperature in the absorber above the hydrocarbon dew point.
 - a). Keep field corrosion inhibitors, soap based lubricants and lube oil out of the amine system.
 - b). Degradation of amine can cause foaming, so avoid it by preventing oxidation and by proper reboiler control.
- a). Maintain the charcoal filter in good working condition, because this is the filter which absorbs the liquid contaminants.
 - b). If these remedies fail, try a de-foaming agent and evaluate the results.
- c). Always keep in mind that the de-foamers are only a temporarily answer for the foaming problem, and the best cure for the problem is to avoid the main causes.

1.4. Corrosion Problem

The corrosion problem is commonly encountered in the amine system and generally occurs in the amine regenerator, heat exchanger, amine stripper and amine pumps etc. Most corrosion occurs in areas where the acid gases are actually released from the solution i.e. in the reboiler, stripper tower and its overhead systems. The cause of corrosion is traced to gaseous H₂S and CO₂ which comes out of the amine solution while the rich amine solution is receiving heat in the heat exchanger prior to the regenerator. These acid gases combine with water to form acids, which will attack the metal surfaces

in contact with the amine solution.

Corrosion problems can be minimized by the following practices:

- 1) Keep the amine solution clean. Do not over load the inlet separator, which prevents solids entering in the system. Other solids that contribute to corrosion are removed by amine filters. so, it's very important to maintain a good amine filtration system.
- 2) The presence of air will cause the amine to degrade into heat stable salts, so there should be a gas blanket on all the amine storage tanks to exclude air.
- 3) Maintain acid-gas loading within the proper ranges.
- 4) Corrosion problems become severe at high temperatures with the rich amine solutions, so keep the amine solution concentration up to the recommended value.
- 5) Amine reboiler temperature should be kept at the recommended range to avoid any amine decomposition or any extra water losses which will affect the amine solution concentration.
- 6) Maintain a regular corrosion testing programmed for an early detection of any corrosion problems in the system.

1.5. Concentration of Residual Gas in Lean Amine Solution

The Concentration of residual gas in the lean amine solution should be controlled at a specified level for the plant. This is the gas which remains in the MDEA solution at all times.

- A) The amount of residual acid gas in the solution depends upon the heat used in the stripper reboiler. Increasing the heat reduces the residual acid gas and vice versa.
- B) If the concentration of residual gas is low, then more acid gas can be absorbed by the lean amine solution in the absorber. This will also, allow a reduction in the circulation rate of the amine solution.
- C) If the inlet sour gas rate changes, the amine solution flow rate and the reboiler heat should be changed in same proportion to match the sour gas changes.

Note: The rich amine solution fed to the amine stripper contains acid gas from two sources:

- a) Acid gas absorbed in the absorber.
- b) Residual acid gas from the amine stripper.

Therefore, the sum of the two is the total acid gas content of the rich amine solution.

1.6. Operating Problem

The cold weather operation requires special attention for

plants using MEA, DEA or Sulfonyl. The freezing point of these solutions is about the same as that of the water. Consequently, lines or vessels in which there is no continuous flow should be given a special consideration during cold weather. If the plant and / or the amine unit are shut down for an extended period during freezing weather, the amine solution should be completely drained from the system.


The freezing point of MDEA and DGA is about (-40 °F) at the recommended amine concentration which is about 50% by weight for MDEA. Therefore, the amine system at the hot areas gas plant does need special attention during the cold weather other than not allowing excessive cooling. As a conclusion, this problem is an occasional one, but it is rather important and must be considered while working in the amine system. Burning fuels, the sulfur is released as sulfur dioxide—an air pollutant responsible for respiratory problems and acid rain [1-6]. Environmental regulations have increasingly restricted sulfur dioxide emissions, forcing fuel processors to remove the sulfur from both fuels and exhaust gases. The cost of removing sulfur from natural gas and petroleum in the United States was about \$1.25 billion in 2008. In natural gas, sulfur is present mainly as hydrogen sulfide gas (H₂S), while in crude oil it is present in sulfur-containing organic compounds which are converted into hydro aluminum oxides and H₂S during the hydro desulphurization [7-9]. In both cases, corrosive, highly-toxic H₂S gas must be converted into elemental sulfur and removed for sale or safe disposal [10-12]. Formation fluids that contain Hydrogen Sulfide-By-product from anaerobic bacterial action on sulfur compounds present in the mud (i.e. Sodium Sulfite)- Thermal degradation of mud additives containing sulfur with tool joint lubricants containing sulfur [13-15].

The H₂S is a weak acid that can go through the following 2 stages when dissolved in water or water based mud: 1. H₂S ↔ H⁺ + HS⁻ - both steps one and two can go back and forth depending on the pH. 2. HS⁻ + OH⁻ ↔ S⁼ + H₂O. Combination of absorption mechanism and magnetic field are used to remove hydrogen sulfide from sour natural gas. Mass transfer rate and mass transfer coefficient is measured and calculated experimentally and theoretically.

2. Materials and Method

Sour gasses which contain different amounts of hydrogen sulfide are reactor bed feed. Two gray 20 lit of volume pressurized vessel contain sour gas can be joint to the experimental line. In 40 cm of efficient volume of glass balls with 2.5 cm in diameter are used as the packing. Two meshes are applied for separating the reactor vessel to the three




sections. One polymeric weir with mesh size of 0.02 cm is on the top of vessel as a holder to let the only treated gas stream.



Control and measuring instruments for pressure, temperature and flow rate evaluation are set in stream lines. All the used valves, pipes and equipment's are corrosion resisted. The bed porosity, e , changes when the number of ball changes, Equation 2 shows the porosity evaluation. V_{nb} is nanoball volume and V is efficient volume of bed.

$$e = 1 - V_{nb}/V. \quad (2)$$

Water is applied to enhance the amount of absorbed H_2S in to the nano fluid. A Nano aluminum oxide particle with 3% wt is mixed with pure water for 180 min and 4000 Watt. This time is considered for stability of nano aluminium oxide into the pure water. This step is an exothermic process. Water helps oxidation of H_2S and also increases the nano aluminium oxide capacity for H_2S absorption. Equation 3, 4, 5, 6 and 7 show the related mechanisms in H_2S adsorption.



After absorption of H_2S into the aluminium oxide nano fluid, the increase in the outlet gas temperature is observed. Also, the increase in temperature is obtained using magnetic fields. Since of some safety limitations, lower appropriate ranges of feed temperature, below 40°C, are chosen beside the application of magnetic field. The basic parameters in operation of a packed bed are evaluated experimentally and theoretically in this paper.

3. Results and Discussion

Totally, the oxygen can be reacting with hydrogen sulfide, and then water molecules and sulfur elements can be produced in the absorption process of sulfur compound removal from sour gas. Changes in the amount of bed porosity are evaluated by measuring pressure drop and minimum velocity. The experiments are done more than minimum velocity values. Pressure drop between top and bottom of fluidized bed is considered. The friction is appeared between the gas stream and the surface of packing's. The correlation 8 shows the effect of friction

factor on pressure drop. This also, affects the friction factor and pressure drop. The higher value of friction factor causes higher values of pressure drops. Although the small changes in values of higher friction factor causes harp change in value of pressure drop.

$$\Delta P = 2E - 161e(204.59f) \quad (8)$$

$$\text{Outlet concentration} = 2 \times 10(2) \text{ Porosity}(2) + .086 \text{ Porosity} - 1.67 \quad (9)$$

Bed porosity, inlet gas temperature, inlet concentration of H_2S , magnetic field which influences the mass transfer area, mass transfer coefficient and rate of reaction are considered here. Three different amounts of porosity are achieved by three groups of packing's. In this case higher porosity presents lower amount of packing's and also lower amount of the mass transfer surface area. In the packed bed the channeling malfunction is occurred. So, the increase trend of C is predicted by increase in the amount of porosity. Outlet concentration below 4 ppm is acceptable result due to commercial rules. Experimental data are in higher values of hydrogen sulfide comparing with ones from modeling data. The correlation 9 shows the trend of outlet hydrogen sulfide concentration with the bed porosity, V_{void}/V . In this experiment, the amounts of the hydrogen sulfide catch from branch line defined the process performance. Inlet sour gas contains 3.4 ppm H_2S , temperature of 33°C is fed into the packed bed with $20m^3/m^3$, $30m^3/m^3$ and $40m^3/m^3$ porosity and also, magnetic field occurred with current of one Ampere.

4. Conclusion

The combination of absorption mechanism and magnetic field are used to remove hydrogen sulfide from sour natural gas. Mass transfer rate and mass transfer coefficient is measured and calculated experimentally and theoretically. The rate of mass transfer is introduced as function of gas temperature, initial concentration of hydrogen sulfide, gas flow rate, magnetic field, nano fluid flow rate and weight concentration of aluminium oxide nano particle in the pure water. The results show, higher value of friction factor causes higher values of pressure drops. Although the small changes in values of higher friction factor causes harp change in value of pressure drop. Moreover, Corrosion problem is commonly encountered in the amine system and generally occurs in the amine regenerator, heat exchanger, amine stripper and amine pumps etc. Most corrosion occurs in areas where the acid gases are actually released from the solution i.e. in the reboiler, stripper tower and its overhead systems. The cause of corrosion is traced to gaseous H_2S & CO_2 which comes out of the amine solution while the rich amine solution is receiving heat in the heat exchanger prior to the regenerator. These acid gases combine

with water to form acids, which will attack the metal surfaces in contact with the amine solution.

References

- [1] L. Carlos, G. Isabel, B. Irene, D. Luis I., R. Luis M. Experimental study of SO₂ and NO_x emissions in fluidized bed oxy-fuel combustion. *Fuel Process Technol.*, 2013; 106: 587–594.
- [2] M. de las Obras-Loscertales, A. Rufas, L. F. de Diego, F. García-Labiano, P. Gayán, A. Abad, J. Adánez, Effects of Temperature and Flue Gas Recycle on the SO₂ and NO_x Emissions in an Oxy-fuel Fluidized Bed Combustor, *Energy Procedia.*, 2013; 37: 1275-1282.
- [3] W. Kaewboonsong, V. I. Kuprianov, N. Chovichien, Minimizing fuel and environmental costs for a variable-load power plant (co-)firing fuel oil and natural gas: Part 1. Modeling of gaseous emissions from boiler units, *Fuel Processing Technology*, 2006; 87: 1085-1094.
- [4] A. Irabien, Environmental and economic evaluation of SO₂ recovery in a ceramic hollow fibre membrane contactor. *Chem Eng Process: Process Inten.*, 2012; 52: 151-154.
- [5] H. Wang, Sh. Li, F. Lai, B. Wang, Computational Model of Greenhouse Gas Emissions of Power Station boiler Considering Desulphurization, *Physics Procedia*, 2012; 24: 44-49.
- [6] D. L. Stern, K. E. Nariman, J. S Buchanan, N. A. Bhole, D. L. Johnson, R. K. Grasselli, The Mobil Oil SO_x Treatment Process (MOST). Catalytic removal of SO_x and H₂S from refinery tail gas, *Catalysis Today*, 2000; 55: 311-316.
- [7] W. Zhou, C. S. Zhao, L. B. Duan, XP. Chen, C. Liang, Two-dimensional computational fluid dynamics simulation of nitrogen and sulfur oxides emissions in a circulating fluidized bed combustor. *Chem. Eng. J.*, 2011; 173: 564-573.
- [8] D. Eow, S. John, Recovery of sulfur from sour acid gas: A review of the technology *Environmental Progress. Americ. Institut. Chem. Eng.*, 2002; 21: 143-162.
- [9] Al Hejami A, Beauchemin D (2019) Effect of sheathing the sample aerosol with hydrogen, nitrogen or water vapour on the analytical performance of solid sampling electrothermal vaporisation coupled to inductively coupled plasma optical emission spectrometry. *J Anal At Spectrom.* <https://doi.org/10.1039/c8ja00266e>.
- [10] Almojjly Abdullah, Johnson Daniel J., Mandale Stephen, Hilal Nidal, Optimisation of the removal of oil in water emulsion by using ceramic microfiltration membrane and hybrid coagulation/sand filter-MF, *Journal of Water Process Engineering*, Volume 27, February 2019, Pages 15-23., <https://doi.org/10.1016/j.jwpe.2018.11.007>.
- [11] Anton L. Esipovich, Anton E. Rogozhin, Artem S. Belousov, Evgeny A. Kanakov, Sergey M. Danov, A comparative study of the separation stage of rapeseed oil transesterification products obtained using various catalysts, *Fuel Processing Technology*, Volume 173, May 2018, Pages 153-164. <https://doi.org/10.1016/j.fuproc.2018.01.023>.
- [12] Bader A., Hartwich M., Richter A., Meyer B., Numerical and experimental study of heavy oil gasification in an entrained-flow reactor and the impact of the burner concept, *Fuel Processing Technology*, Volume 169, January 2018, Pages 58-70. <https://doi.org/10.1016/j.fuproc.2017.09.003>.
- [13] Bisht Harender, Shankar Balachandran Vijai, Patel Mitra, D. Sharma Girish, H. Yadav Ashwani, D. Biswas Dwaipayan, Pacharu Sreenivas, Mandal Sukumar, K. Das Asit, Effect of composition of coke deposited in delayed coker furnace tubes on on-line spalling, *Fuel Processing Technology*, Volume 172, April 2018, Pages 133-141. <https://doi.org/10.1016/j.fuproc.2017.12.013>.
- [14] Yamakawa Soji, Shimada Kenji, Feature Edge Extraction Via Angle-Based Edge Collapsing and Recovery, *J. Comput. Inf. Sci. Eng.* 2018; 18 (2): 021001-021001-18. doi: 10.1115/1.4037227.
- [15] Cheng Yao, Du Xiaoping, Toward the Effect of Dependent Distribution Parameters on Reliability Prediction, *J. Comput. Inf. Sci. Eng.* 2018; 18 (2): 021008-021008-10. doi: 10.1115/1.4039193.
- [16] Toke Christensen Esben, I. J. Forrester Alexander, Lund Erik, Lindgaard Esben, Developing Metamodels for Fast and Accurate Prediction of the Draping of Physical Surfaces, *J. Comput. Inf. Sci. Eng.* 2018; 18 (2): 021003-021003-12. doi: 10.1115/1.4039334.
- [17] Mourtzis Dimitris, Milas Nikolaos, Vlachou Aikaterini, An Internet of Things-Based Monitoring System for Shop-Floor Control, *J. Comput. Inf. Sci. Eng.* 2018; 18 (2): 021005-021005-10. doi: 10.1115/1.4039429.
- [18] Zhang Binbin, Jaiswal Prakhar, Rai Rahul, Nelaturi Saigopal, Additive Manufacturing of Functionally Graded Objects: A Review, *J. Comput. Inf. Sci. Eng.* (2018); doi: 10.1115/1.4039683.